



Wels, March 6th 2017

FRONIUS SNAPINVERTER INTEGRATED DC-SWITCH-DISCONNECTORS IEC 60947-3:2015 - DC-PV2 COMPLIANCE

Fronius International GmbH

hereby confirms that all inverter types of the Fronius SnapInverter generation

- / **Fronius Galvo 1.5-1 to Fronius Galvo 3.1-1**
- / **Fronius Primo 3.0-1 to Fronius Primo 8.2-1**
- / **Fronius Symo 3.0-3-S to Fronius Symo 5.0-3-S**
- / **Fronius Symo Hybrid 3.0-3-S to Fronius Symo Hybrid 4.5-3-S**
- / **Fronius Symo 3.0-3-M to Fronius Symo 8.2-3-M**
- / **Fronius Symo 10.0-3-M to Fronius Symo 12.5-3-M**
- / **Fronius Symo 15.0-3-M to Fronius Symo 20.0-3-M**
- / **Fronius Eco 25.0-3-S to Fronius Eco 27.0-3-S**

are original equipped with switch disconnectors for operation under all applicable load conditions and also fault conditions.

These switches are compliant and fulfill the listed requirements according to the utilization category **DC-PV2** for making and breaking capacity.

(As defined in the standard: IEC 60947-3 :2015 - Low-voltage switchgear and control gear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units, incl. amendments 1 + 2)

Fronius International GmbH

Solar Energy Division
Froniusplatz 1
A-4600 Wels

A handwritten signature in blue ink, appearing to read "Thomas Mühlberger".

DI Thomas Mühlberger
Head of Solution Management